



SPEC DATA SHEET



- High-quality fabric finished baffle
- Excellent acoustical performance
- Standard, designer or C.O.M. fabrics
- Custom sizes and shapes
- Easy to install

AMS[®]

RIGID ACOUSTICAL BAFFLES

AMS Rigid Baffles are ideal for customers that are looking for a hanging baffle with “crisp” corners, a fabric finish and high acoustical ratings to tame reverberation in reverberant echo prone interiors.

FINISHES

AMS uses Burch Primetime as our standard fabric. A much more cost effective and aesthetically pleasing option than Guilford of Maine FR701 Style 2100 which is the industry standard and we also offer as a standard option. Hundreds of approved decorative fabrics are also available from numerous manufacturers including, but not limited to: Guilford of Maine, Maharam, Design Tex and Knoll. Customers may also specify their own fabric, provided the material meets manufacturing requirements.

ACOUSTICAL

NRC Rating

1” Thick ————— .80 – .90

2” Thick ————— 1.05 – 1.15

SIZING

Rigid Baffles are available in a 1” or 2” thickness. Standard sizes are 2’ x 4’ and 4’ x 8’, with custom sizes up to a maximum of 4’ x 10’.

SUBSTRATE


6-7# PCF rigid fiberglass core with optional chemically hardened edges

FIRE RATING

All components shall have a Class A fire rating per ASTM E-84

MOUNTING OPTIONS

The Rigid Baffles include brackets or tabs that extend upwards from the top of the baffle so the baffle can be installed or hung down vertically from the ceiling.



Acoustic Material Supply
Office: 214.234.9935
www.acousticmaterialsupply.com