



- Standard size 2' x 2' or 2' x 4'
- Custom sizes available
- 1" or 2" thickness
- White nubby cloth facing
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements



Acoustic Material Supply

Office: 214.234.9935

www.acousticmaterialsupply.com

AMS S-2000 Acoustical & Barrier CEILING TILES

AMS® S-2000 Acoustical & Barrier Ceiling Tiles are offered as both a sound absorbing as well as a combination sound absorbing/ sound blocking tile.

S- 2000 Ceiling Tiles have a 2 mil white pebble grain vinyl facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

S-2000B Ceiling Tiles take the standard S-2000 tile and add a 1# per square foot foil backed vinyl noise to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

FINISH

White nubby cloth facing

ACOUSTICAL

NRC Rating

1" _____ .85

2" _____ 1.15

B Version _____ STC 26

SUBSTRATE

6-7# PCF rigid fiberglass core

***S-2000B adds a vinyl noise barrier**

EDGE DETAIL

Square

WEIGHTS

S-2000 Tile .6 lbs/ SqFt

S-2000B Tile 1.6 lbs/ SqFt

MOUNTING OPTIONS

Grid supplied by others